

PRESSURE RATINGS PLAIN AND RED LINE TUBING

O.D.12.6±0.4mm Wall 2.2±0.3mm

Length		Max. Pressure No Corrosion @ 65C (150°F)		Steam Boiler Service up to 210C (425°F)	
Inches	mm	Standard	Red Line	Standard	Red Line
8	203	460	390	340	300
10	254	445	370	335	295
12	305	435	360	325	295
14	356	415	345	315	290
15	381	405	*	310	*
16	406	400	335	300	285
18	457	385	325	295	280
20	508	375	310	285	280
22	559	355	*	280	*
24	610	340	280	270	270
30	762	295	250	*	*
36	914	260	215	*	*
48	1219	205	175	*	*
60	1524	155	135	*	*
72	1829	110	100	*	*
*	2000	85	75	*	*

O.D.15.4±0.4mm Wall 2.4±0.3mm

Length		Max. Pressure No Corrosion @ 65C (150°F)		Steam Boiler Service up to 210C (425°F)	
Inches	mm	Standard	Red Line	Standard	Red Line
8	203	435	370	320	280
10	254	420	345	315	275
12	305	410	335	305	275
14	356	390	325	295	270
15	381	380	*	290	*
16	406	375	315	285	265
18	457	360	305	280	260
20	508	350	290	270	260
22	559	335	*	265	*
24	610	320	265	255	250
30	762	280	235	*	*
36	914	245	205	*	*
48	1219	195	165	*	*
60	1524	150	125	*	*
72	1829	100	90	*	*
*	2000	75	65	*	*

O.D.18.6±0.4mm Wall 3.0±0.3mm

Length		Max. Pressure No Corrosion @ 65C (150°F)		Steam Boiler Service up to 210C (425°F)	
Inches	mm	Standard	Red Line	Standard	Red Line
8	203	425	360	315	280
10	254	410	340	310	275
12	305	400	330	300	275
14	356	385	320	290	270
15	381	375	*	285	*
16	406	370	310	280	265
18	457	355	300	275	260
20	508	345	285	265	260
22	559	330	*	260	*
24	610	315	260	250	250
30	762	275	230	*	*
36	914	240	200	*	*
48	1219	190	160	*	*
60	1524	145	125	*	*
72	1829	100	100	*	*
*	2000	75	65	*	*